AC-630

more compact ● higher capacity 25 PSI MAOP, 1320 cfh at 2-inch w.c. differential





AC-630

- Convoluted diaphragms
- Unique valve design
- Smaller meter profile
- Superior corrosion resistance
- · Regular or TC tangent
- Automatic meter reader capability
- Permanent lube bearings
- 20 LT, 30 LT, 45 LT and #3-4 Sprague connection sizes
- Full warranty
- Pointer or odometer index





WEIGHT = 21 lbs.

Reference Materials

Installation Instructions	AIM-3715
Operation/Maintenance	
Manual & Video	52722P002
Repair Parts List	RPL-3850

AMC Quality System QMI is Accredited by:





SAVE MONEY -

on installation and maintenance with the AC-630. Long-term performance is proven with 40 years of craftsmanship that have gone into its development. Plus, just one serviceperson is needed to install the 21 lb. AC-630, reducing your costs and lowering the possibility for injury.

Rated Gas Capacity For 0.60 S.G. Gas

1	Inlet Pressure PSIG	Inches W.C. Differential	Capacity SCFH
	.25	1/2"	630 ^{1,2}
	.25	2"	1320
	1	2"	1340
	2	2"	1390
	5	2"	1515
	10	2"	1710
	15	2"	1890
	20	2"	2010
	25	2"	2160

1 - Propane - 397 cfh 2 - Butane - 347 cfh





Order Information:

Model No.:	
Regular or Temperature Compensated:	
U.S. or Metric:	
Size of Connection:	
Type of Index:	
Proof Preference: 100 +/- 1%	
Standard Color or ASA #49 Grey:	

Contact American Meter with any questions or orders at the address and phone number below.

American Meter Company has a program of continuous product development and improvement and, therefore, the information in this bulletin is subject to change or modification without notice.



Yesterday...Today...Tomorrow

300 Welsh Road, Building One Horsham, PA 19044-2234 Phone: 215/830-1800 Fax 215/830-1890 www.americanmeter.com CANADIAN METER

275 Industrial Road Cambridge, Ontario Canada N3H 4R7 Phone: 519/650-1900 Fax 519/650-1717 www.americanmeter.com

ELSTER 🧇 AMCO