

The new A.Y. McDonald Bottom Suction-Cistern Pump is a durable product that delivers high performance for clear water, gray water, or filtered effluent service operations. Its unique bottom suction design provides maximum drawdown without decreasing the pump's overall longevity.

The Bottom Suction-Cistern pump can pass solids up to 1/8". The bottom suction pumps are intended for use in cistern or tank applications. These pumps are well suited to meet agricultural, residential, and commercial installation needs



| Model No. | Description                | HP  | Carton Qty | Volt | Run Amp. | Wt.   |
|-----------|----------------------------|-----|------------|------|----------|-------|
| 22050L2AB | Bottom Suction Sub Pump 2W | 1/2 | 1          | 115  | 9.5      | 19.00 |
| 22075L2AB | Bottom Suction Sub Pump 2W | 3/4 | 1          | 115  | 12       | 23.00 |
| 22050L2B  | Bottom Suction Sub Pump 2W | 1/2 | 1          | 230  | 6.8      | 19.00 |
| 22075L2B  | Bottom Suction Sub Pump 2W | 3/4 | 1          | 230  | 6.8      | 23.00 |

## Features:

- Bottom suction
- Quiet operation
- Corrosion resistant
- Available in 115V & 230V
- CSA listed

## **Applications:**

- Dirty water applications
- Rain water collection
- Pond applications
- Cisterns for both clean & dirty water
- Potable water
- Vertical or Horizontal installation

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



**A.Y. McDonald Mfg. Co.** P.O. Box 508 Dubuque, IA 52004-0508

**Toll Free:** 1-800-292-2737 **Fax:** 1-800-832-9296 **Hours:** 7:00 a.m. - 5:00 p.m., CST sales@aymcdonald.com www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

## Submitted by: