

SUBMITTAL DATA SHEET


Sump, Sewage, & Effluent Pumps

DuraMAC™ | Guardian

747H20 - Guardian



Designed for ground water, sump crocks in homes, motels, hotels, schools, hospitals, industrial buildings, computer and record storage rooms.



Water Removed Feet of Lift - GPH Removed

Inlet Pressure (PSI)	30	390
	40	630
	60	906
	80	1110



BACKFLOW OPTIONS ORDER MODEL

747H20-0001**

BACKFLOW PROVIDED

3/4" Reduced pressure assembly

ASSE STANDARD

1013

OTHER APPROVALS

Approved by the Foundation for Cross-Connection Control and Hydraulic Research at the University of Southern California

Model No.	Description	Wt.
747H20	Guardian	11
747H20A	w/ Tank Alert Alarm	16
747H20-0001	Guardian w/ RPZ	16

**Where required by code

SUBMITTAL INFORMATION

- Made in the USA
- Patented activation valve for Positive ON, Positive OFF
- Designed for intermittent or continuous use
- Supplied with single check valve for your convenience
- Made with high quality brass and PVC materials for corrosion resistance
- Designed for de-watering
- Discharge size 1 1/4" PVC Sch. 80 (IPS)
- 3/4" FNPT inlet
- Minimum pressure 29 PSI, maximum 90 PSI
- Minimum water temperature 32°F.

Tank Alert Liquid Level Alarm - 747H20A / 747H20RRA

Tank Alert AB (6190-137 - 120V, Nema1 enclosure

- with mechanical switch, normally open, SignalMaster® float 15' cord, high water alarm with pipe mounting clamp)

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



A.Y. McDonald Mfg. Co.
P.O. Box 508
Dubuque, IA 52004-0508

Toll Free: 1-800-292-2737
Fax: 1-800-832-9296
Hours: 7:00 a.m. - 5:00 p.m., CST

sales@aymcdonald.com
www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by: