

Model# 0194-LE60-AD0

Two Handle Shell Type Wallmount Pre-Rinse Faucet

FEATURES & SPECIFICATIONS

- 2-3/8" Lever Handle
- 24" Quick Install Riser With Spring Guide
- 44" Flexible Stainless Steel Hose
- Replaceable Seats
- Back Flow Preventers
- 1.1 GPM Flow Rate, 6.5 ozf Spray Force Spray Valve
- 1.1 GPM Flow Rate, 6.5 ozf Spray Force Spray Valve
- 2-Hole 4" Installation
- Pipe Strap and Hook Assembly
- Secondary Control Valve
- Add-On Faucet
- 6" Swivel Tube Spout



FINISHES

- PC Polished Chrome

STANDARDS

- ASME A112.18.1
- ANSI / NSF 61, SECTION 9
- CUPC / IAPMO LISTED
- ANSI A117.1 / ADA COMPLIANT
- CONTAINS NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT



FLOW

- 1.1 GPM Flow Rate, 6.5 ozf Spray Force Spray Valve

WARRANTY

- Lifetime Limited Warranty
- Lifetime Residential Warranty
- 5 Year Commercial Warranty

Job Name _____ Date _____

Model Specified _____ QTY _____

Customer/Wholesaler _____

Contractor _____

Architect/Engineer _____

Submitted as Shown _____


Submitted w/ Variations _____

0194-LE60-AD0/REV. 11 2016

Product Specifications subject to change without notice

Model# 0194-LE60-AD0

Two Handle Shell Type Wallmount Pre-Rinse Faucet



0194-LE60-AD0/REV. 11 2016

Product Specifications subject to change without notice