DWV PIPE SUPPORT

>> 549-7 SERIES

SPECIFICATION

Sioux Chief's 549 series StickEmUp[™] pipe support shall be used where necessary to support Schedule 40 DWV piping on residential single family and multi-family projects. Pipe support cradle shall be designed to flex so that each model number supports two different pipe sizes for pipes ranging from 1½" through 4". Hanger shall include two preloaded, ring-shank nails and feature I-beam design for strength and rigidity. Pipe support shall be IAPMO certified.

INSTALLATION

Follow national code requirements for proper pipe slope, when applicable. Secure pipe support to stud, joist or form board with nails. Position cradle around pipe either vertically or horizontally. If desired, apply multi-purpose glue. Acceptable installations include vent riser clamp applications on plastic pipe within stud walls. Pipe support can also be secured to form boards prior to a concrete pour to prevent pipe movement.

MATERIALS

Hanger: ABS, U.V. resistant, corrosion proof, impact resistant **Nail:** 1⁵/₈" continuous ring shank, zinc-plated

SAFE WORKING LOAD

25 lbs.

DIMENSIONS

	549-712	549-734
A: Length	11.71"	13.16"
B: Stem length	10"	10"
C: Stem width	0.875"	0.875"
D: Stem depth	0.5"	0.5"
E: Nail holes	1" on center	1" on center
F: Cradle diameter	1.88"	3.5"







Choose Item Number

549-7A e.g. 549-712: StickEmUp[™] for 1½"-2" DWV pipe CRADLE SIZE A 12 = 1½"-2" DWV pipe 34 = 3"-4" DWV pipe

