# **CAST IRON SQUARE FLOOR SINK**

## >> 861 SERIES

### **SPECIFICATION**

Sioux Chief 861 Series cast iron floor sink shall be used where necessary in drainage systems or where PVC floor sinks are not permitted. Floor sink shall have an acid resisting porcelain enamel coating (ARE) for superior sanitation, and a high heat discharge rating for commercial hot water drainage applications. Connection to pipe and trap assembly shall be made by means of a no-hub coupling. Grates shall be available in various patterns for intended use. Sump area shall have smooth inner surfaces for quick and complete drainage. Designed in accordance with ASME A112.6.7-2001

### MATERIALS

**Ring/strainer:** Nickel-bronze, porcelain-coated cast iron **Drain body:** Porcelain-coated cast iron **Clamping collar:** Cast aluminum

#### DIMENSIONS

| <b>A</b> : | Overall height* | 85%"  |
|------------|-----------------|-------|
| B:         | Sump height*    | 61⁄8" |
| <b>C</b> : | Top diameter*   | 12"   |
| D:         | Sump width      | 81⁄4" |
| E:         | Top to flange   | 2"    |

\*Nickel-bronze strainer adds 1/2" to overall height, and 3/4" to top diameter

| ITEM # SUBMITTED |     |  |
|------------------|-----|--|
| JOB NAME         |     |  |
| LOCATION         |     |  |
| ENGINEER         |     |  |
| CONTRACTOR       |     |  |
| PO#              | TAG |  |



861-23XF



#### **Create Item Number**

# 861-<u>ABC</u>

e.g. 861-23Xi2W: Porcelain-coated cast iron square floor sink with open-half ARE grate, stainless steel debris screen, and 3" no-hub connection

- **22** = 2" cast iron no-hub
- **23** = 3" cast iron no-hub
- 24 = 4" cast iron no-hub

#### FLANGE B

- X = No flangeXF = With flange
- OPTIONS <u>C</u>
  - i = Full ARE cast iron grate
  - i2 = Open-half ARE cast iron grate
  - i3 = Open-quarter ARE cast iron grate
  - $\mathbf{N}$  = Full nickel-bronze grate
  - **N2** = Open-half nickel-bronze grate
  - **N3** = Open-quarter nickel-bronze grate
  - **W** = Stainless steel debris screen
  - $\mathbf{D}$  = Aluminum dome bottom strainer
- C = Clamping collar with bolts\*\*For use with flanged floor sink

| 861-52i  | Open-half grate, porcelain-coated cast iron    |
|----------|--|
| 861-53i  | Open-quarter grate, porcelain-coated cast iron |
| 861-5i   | Full grate, porcelain-coated cast iron         |
| 861-52iN | Open-half grate with frame, nickel-bronze      |
|          |  |

Available Separately:

- 861-53iN Open-quarter grate with frame, nickel-bronze
- 861-5iN Full grate with frame, nickel-bronze
- 861-AC Two-piece aluminum flashing collar with bolts
  - 861-UMi Stainless steel debris screen 861-AD Aluminum dome bottom strainer
- 863-FA Round aluminum condensate funnel
- 863-FN Round nickel condensate funnel
- 863-FN0 Oval nickel condensate funnel

