## 

# UT445U(V)

### 0.125GPF High-Efficiency Washout Urinal

#### FEATURES

- Full size urinal with concealed integral trap
- Washout flush action with 3/4" top or back spud inlet
- 0.125 GPF with any TOTO flush valve shown below
- Complete with low profile dome strainer

#### MODELS

- UT445U Urinal with 3/4" top spud inlet
- UT445UV Urinal with 3/4" back spud inlet

#### ADDITIONAL ITEMS

FLUSH VALVES	
EcoPower®	
TEU1UA12#CP	0.125GPF
TEU2UA11#SS	0.125GPF
TEU3UA11#SS	0.125GPF

#### COLORS/FINISHES

• #01 Cotton

#### PRODUCT SPECIFICATION

The wall-mounted, ADA compliant, high-efficiency washout urinal shall be 0.125GPF/0.473LPF when paired with a TOTO 0.125GPF flushometer valve. Urinal specified shall be TOTO Model UT445U\_\_.

Flush valve specified shall be TOTO Model \_\_\_\_\_



#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1,
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, CALGreen Title 24, California Energy Commission Standards
- ADA compliant



#### 0.125GPF High-Efficiency Washout Urinal

#### **SPECIFICATIONS**

- Water Use 0.125GPF/0.473LPF
- Flush System
  Washout flush action
- Warranty One Year Limited Warranty
- Material Vitreous china
- Min. Water Pressure 15 psi (flowing)
- Height (Urinal Only) 26"
- Width 17-3/4"
- Rim 14-1/4"
- Shipping Weight UT445U(V) 60lbs
- Shipping Dimensions UT445U(V) 29" L x 18" W x 16" H

#### INSTALLATION NOTES

Ultra-low high efficiency urinals require a system with a minimum 2% slope. Maximum drainage capacity rated at 6.6 gal/min (25 L/min). Adjust angle stop accordingly to prevent overflow. Confirm with local codes and standards for floor drain requirement.



**TOTO**<sub>®</sub>