EIGHT COMMERCIAL

TAG

Design and Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



Wall Thickness In. [mm]	'A' Overall Length In. [mm]	Approx. Wt. Lbs. [kg]
4 [102]	8-5/8 [219]	2 [1]
6 [152]	10-5/8 [270]	2 [1]
8 [203]	12-5/8 [321]	3 [1]
10 [254]	14-5/8 [371]	3 [1]
12 [305]	16-5/8 [422]	4 [2]
14 [356]	18-5/8 [473]	4 [2]

ENGINEERING SPECIFICATION: ZURN Z1345

Exposed non-freeze anti-siphon automatic draining wall faucet complete with exterior chrome finish, brass casing, all bronze interior parts, antisiphon integral vacuum breaker, operating rod with free-floating compression closure valve, wall support, replaceable seat washer, combination 1/2 [13] female solder inlet and 1/2 [13] male IP inlet connection, and 3/4 [19] male hose connection.

OPTIONS (Check/specify appropriate options)

SUFFIXES

CP3	3/4 [19] Male Pipe Thread x 3/4 [19] Female Solder
	Hydrant Guard
HGS	Hydrant Guard Stem
RK	Hydrant Parts Repair Kit

* IMPORTANT - To assure drainage Turn sillcock handle to closed position and detach hose from spout during freezing weather. If hose is left attached, the frost-proof sillcock cannot drain properly and trapped water may freeze and damage sillcock.

- ** The frost-proof sillcock assures no-freeze operation because the valve mechanism shuts off water inside the building, where it is heated. If building will be unheated for any length of time, then all water lines should be drained and plumbing fixtures winterized.
- ** Maximum recommended operating pressure: 125 PSI Water temperature range: 40 - 130° F



▲ WARNING: Cancer and Reproductive Harm - <u>www.P65Warnings.ca.gov</u>
 ▲ ADVERTENCIA: Cáncer y daño reproductivo - <u>www.P65Warnings.ca.gov</u>
 ▲ AVERTISSEMENT: Cancer et effets néfastes sur la reproduction - <u>www.P65Warnings.ca.gov</u>

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA 16502, Ph. 855.663.9876

In Canada | Zurn Industries Limited 7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6, Ph. 877.892.5216
 Rev.
 E

 Date:
 03/24/2022

 C.N. No.
 144386

 Prod. | Dwg. No. Z1345 | 63821